



Compact cold-water high pressure cleaner. With its compact dimensions, robust construction and greatest possible manoeuvrability, this unit is a credit to the compact class.



1 Automatic pressure cut-off

- For reduced energy and water consumption.
- Switches off immediately when work is interrupted.

2 Extendable push handle

- Large aluminium profiles ensure stability and easy turning manoeuvre.
- Acts as an accessory holder when extended.

3 Pump technology

- High-quality components, such as brass cylinder head and chromium-plated stainless steel pistons ensure a long service life.
- Direct drive with minimal moving parts, low maintenance, optimal efficiency.

4 Accessory storage

- Clever features such as nozzle storage for added convenience.
- On-board cord storage with clip.



HD 5/11 C

- Extended trigger gun
- Stainless steel spray lance
- Entry-level model for mobile applications

Technical data

Order No.	1.520-100.0	
EAN code	4039784717077	
Supply voltage	Ph / V / Hz	1 / 230 / 50
Flow rate	l/h	500
Working pressure	bar / MPa	115 / 11.5
Max. pressure	bar / MPa	130 / 13
Max. water inlet temperature	°C	60
Connection load	kW	2.2
Weight	kg	19
Dimensions (L × W × H)	mm	360 × 375 × 925

Equipment

Spray gun	Extended high-pressure trigger gun	
Pressure hose	m	10
Spray lance	mm	400
Triple nozzle (0°/25°/40°)	Manual	
Anti-twist system	■	
Pressure cut-off	■	
Servo Control	-	

■ Included in delivery.

Accessories for HD 5/11 C 1.520-100.0

KÄRCHER



	Order No.	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides							
High-pressure hose, 15 m, ID 8, 315 bar, including rotary coupling	1	6.390-010.0	ID 8	315 bar	15 m		▲
High-pressure hose, 20 m, ID 8, 315 bar, extension piece	2	6.390-031.0	ID 8	315 bar	20 m		▲
High-pressure hose, 15 m, ID 10, 220 bar, extension piece	3	6.390-023.0	ID 10	220 bar	15 m		▲
High-pressure hose, 10 m, ID 8, 315 bar, extension piece	4	6.391-342.0	ID 8	315 bar	10 m		▲
High-pressure hose, 30 m, ID 8, including rotary coupling	5	6.390-293.0	ID 8	315 bar	30 m		▲
Longlife 400 with unions on both sides							
High-pressure hose Longlife 400, 10 m, ID 8, including rotary coupling	6	6.388-083.0	ID 8	400 bar	10 m	10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 x 1.5, with kink protection.	▲
High-pressure hose Longlife 400, 20 m, ID 8, extension	7	6.390-027.0	ID 8	400 bar	20 m	with rotary coupling, 2 x M 22 x 1.5	▲
High pressure hose ID 6, 10 m, including rotary coupling	8	6.391-883.0	ID 6	400 bar	10 m	With rotary coupling, 2 x M 22 x 1,5	▲
Longlife 400 high-pressure hose, 10 m, DN 8, extension piece	9	6.391-354.0	ID 8	400 bar	10 m		▲
High-pressure hose Longlife 400, 15 m, ID 8, including rotary coupling	10	6.389-709.0	ID 8	400 bar	15 m	With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 30 m, ID 8, including rotary coupling	11	6.390-294.0	ID 8	400 bar	30 m		▲
High-pressure hose 1.5 m, ID 8, including connectors	12	6.390-178.0	ID 8	400 bar	1.5 m	1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	□
Food industry version with unions on both sides							
High-pressure hose, 10 m, DN 8, suitable for the food industry, extension piece	13	6.389-479.0	ID 8	250 bar	10 m	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	▲
High-pressure hose, 20 m, ID 8, suitable for food industry, extension piece	14	6.389-581.0	ID 8	250 bar	20 m	20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	▲
Longlife food design with screw connections at both ends							
High pressure hose food ID 8, 10 m	15	6.391-864.0	ID 8	400 bar	10 m	Longlife HP hose for use in the food industry. Außendecke##	▲
High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling	16	6.391-887.0	ID 8	400 bar	20 m	animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5	▲
Standard							
High-pressure hose, 10 m, ID 6, AVS trigger gun connector	17	6.391-238.0	ID 6	250 bar	10 m	10 m high-pressure hose (M 22 x 1.5) with kink protection.	■
	18	6.110-034.0	ID 6	250 bar	10 m	With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.	■
High-pressure hose, 15 m, ID 6, AVS gun connection	19	6.391-394.0	ID 6	250 bar	15 m		□
High-pressure hose, 10 m, ID 6, 300 bar, AVS trigger gun connection	20	6.391-875.0	ID 6	300 bar	10 m	With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar	□
Longlife 400							
Longlife 400 high-pressure hose, 10 m, DN 6, M 22 x 1.5	21	6.391-882.0	ID 6	400 bar	10 m	With patented AVS connection in the trigger gun (pivot-mounted).	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.	ID	Max. working pressure	Length	Price	Description	
Longlife 400 high-pressure hose, 10 m, DN 8,	22	6.391-351.0	ID 8	400 bar	10 m			<input type="checkbox"/>
Food industry version								
High-pressure hose, 15 m, ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey	23	6.391-654.0	ID 6	250 bar	15 m		15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.	<input type="checkbox"/>
Longlife food design								
High-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun connection	24	6.391-888.0	ID 6	400 bar	15 m		Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	<input type="checkbox"/>
Special hoses								
High-pressure hose 1.5 m, ID 8, including connectors, outlet bend	25	6.388-886.0	ID 8	400 bar	1.5 m			<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.	Flow rate				Price	Description	
Easy Press high-pressure trigger gun with holding force reduction (Kärcher patent)									
Extended Easy Press trigger gun	1	4.775-529.0						Extended easy press high-pressure trigger gun for high-pressure hoses with rotating connector.	■
Trigger guns									
High-end HP trigger gun	2	4.775-823.0							□
Quick connect									
Quick coupling	3	6.401-458.0						For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female.	□
Male coupling	4	6.401-459.0						Hardened stainless steel nipple for quick coupling 6.401-458. With M22 x 1,5 male.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.	Max. working pressure	Nozzle size		Price	Description	
Triple nozzles								
Triple nozzle 036	1	4.767-148.0	300 bar	36			Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.	■
Triple nozzle, touchless changeover								
Triple nozzle, touchless changeover	2	4.767-001.0		34			Triple nozzle with high-pressure pencil jet (25°) and low-pressure fan jet (40°). Fast and easy jet changeover by turning the nozzle.	□
Dirt Blaster, small								
Dirt blaster	3	4.767-022.0	180 bar	35			Small rotary nozzle for dirt blaster. The rotating point jet achieves 10 times the cleaning performance. Outstanding working time thanks to ceramic nozzle and bearing ring. Max. 180 bar/18 MPa, 60°C.	□
Dirt blaster, large								
Dirt blaster	4	4.763-931.0	300 bar	35			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.	Max. working pressure	Length		Price	Description	
Spray lance								
550 mm lance, non-rotatable	1	4.760-665.0		550 mm			550 mm stainless steel lance. With manual coupling. Non-rotatable.	■
250 mm lance, non-rotatable	2	4.760-667.0		250 mm			250 mm stainless steel lance. With manual coupling. Non-rotatable.	□
Angular spray lance								
Spray lance for toilets and rain gutters	3	4.760-073.0					Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	□
Double lance								
Double lance 960 mm	4	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	□
Flexible spray lance								
Flexible lance 1050 mm	5	6.394-654.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	□
Telescopic spray lance								
Telescopic spray lance	6	6.394-690.0	225 bar					□
Strap for telescopic spray pipe	7	6.373-987.0					Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.	□
Gutter cleaner								
Gutter cleaning lance	8	2.642-305.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.		Dummy	Dummy	Dummy	Price	Description	
Miscellaneous									
Backflow check valve	1	6.412-578.0	-					To prevent cleaning agent from entering the drinking water system at low supply pressure.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.	Flow rate	Nozzle size	Diameter	Price	Description	
Hard surface cleaner FR 30								
FR 30	1	2.642-997.0			300 mm			<input type="checkbox"/>
FR 30 Me surface cleaner								
Hard surface cleaner FR 30 Me	2	2.640-355.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	<input type="checkbox"/>
Machine-specific nozzle kits for FR								
Nozzle kit for surface cleaners	3	2.640-482.0	450-500 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h).	<input type="checkbox"/>
FR Basic surface cleaner								
FR Basic surface cleaner	4	2.642-998.0			300 mm		FR Basic: entry level model for splash-free cleaning of surfaces indoors and outdoors. Plastic casing and simple ceramic bearing. Includes nozzle kit. Max. 180 bar, 600 l/h, 60°C.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.	Nozzle size				Price	Description	
Power nozzle spray angle 25°									
Power nozzle spray angle 25°	1	2.883-821.0	36					Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	<input type="checkbox"/>
25° power nozzle for cleaning agent suction	2	2.884-521.0	250						<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.	Length				Price	Description	
Automatic, self-winding hose reels									
Automatic hose reel, coated	1	2.639-919.0	20 m					Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
Powder-coated swivel holder	2	2.639-931.0						Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	<input type="checkbox"/>
Automatic hose reel, stainless steel, includes swivel holder	3	6.391-421.0	20 m					Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
Automatic hose reel, powder-coated steel / plastic	4	6.392-975.0	20 m					Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	<input type="checkbox"/>
Automatic stainless steel / synthetic material hose drum	5	6.392-965.0	20 m					Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	<input type="checkbox"/>
ABS automatic stainless steel hose drum	6	2.641-866.0	20 m					High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	<input type="checkbox"/>
ABS pivoting stainless steel wall bracket	7	2.641-867.0						Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.	Length	Diameter		Price	Description	
Starting current limiter								
Starting current limiter	1	2.637-495.0					Reduces starting current in single-phase supply and protects line fuse.	<input type="checkbox"/>
Geka coupling								
Geka connector with hose barb, R 1/2"	2	6.388-461.0					with hose liner	<input type="checkbox"/>
Geka connector with hose barb, R 3/4"	3	6.388-455.0						<input type="checkbox"/>
Geka connector with inner thread, R 3/4"	4	6.388-473.0					with female thread	<input type="checkbox"/>
Suction filter								
Suction filter with check valve	5	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	<input type="checkbox"/>
Water suction filter	6	6.414-956.0						<input type="checkbox"/>
Water fine filter								
Water fine filter, with adapter	7	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	<input type="checkbox"/>
Water supply hose								
Water supply hose	8	4.440-038.0	7.5 m				NW 13 R1" / R 3/4", up to 30 °C	<input type="checkbox"/>
	9	4.440-207.0	7.5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	<input type="checkbox"/>
Backflow check valve								
Backflow preventer	10	2.641-374.0					To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.	Flow rate				Price	Description	
Rotating washing brush									
Rotating wash brush for < 800 l/h machines, natural hair bristles	1	4.762-560.0	500-800 l/h						<input type="checkbox"/>
Rotating wash brush for < 800 l/h machines, nylon bristles	2	4.762-561.0	500-800 l/h					The rotating wash brush gently removes fine dust and grime from all surfaces. Heat-resistant up to 60°C. (M 18 x 1.5, replaceable brush insert).	<input type="checkbox"/>
Push-on washing brush									
Push-on washing brush	3	4.762-016.0						Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	<input type="checkbox"/>
Push-on wash brush	4	4.762-497.0						The wash brush is fitted directly onto the devices' new dual and triple nozzles using clamping.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



1-3

		Order No.	Max. working pressure	Nozzle size	Diameter	Price	Description	
Pipe cleaning nozzle								
Pipe cleaning dirt blaster D 25 / 040	1	6.415-944.0		40	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	<input type="checkbox"/>
Pipe cleaning dirt blaster D 30 / 040	2	6.415-946.0		40	30 mm			<input type="checkbox"/>
Pipe cleaning dirt blaster D 35 / 040	3	6.415-948.0		40	35 mm			<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

Accessories for HD 5/11 C 1.520-100.0



		Order No.	Flow rate				Price	Description	
Cup foam lance									
Cup foam lance	1	6.394-668.0	1200 l/h					Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.	<input type="checkbox"/>
1-litre cleaning agent container for foam lance	2	6.414-954.0							<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.