



IVC 60/30 Ap

The compact IVC 60/30 Ap industrial vacuum is ideal for manufacturing areas and production machinery. Its side channel blower is wear-resistant, making the vacuum ideal for continuous use.



1 Wear-resistant side channel blower

- A side channel blower delivers high suction power with a very long lifetime of at least 20,000 hours. These machines are therefore ideal for multiple shift operation.

3 Waste container with set-down mechanism

- The waste container with set-down mechanism ensures ergonomic emptying, even when the vacuumed waste is heavy.

2 Automatic Filter Cleaning System Tact²

- The two filters are cleaned with targeted, powerful blasts of air. The procedure is triggered automatically, the suction power remains constantly high, and the work can be continued without interruption.
- Filter designed to allow uninterrupted use with constant high suction power.

4 With compact flat pleated filter

- The compact flat pleated filter allows a large filter area with a small and clear design.



IVC 60/30 Ap

- Anti-static equipment
- Manual filter cleaning
- Integrated cyclone for pre-separation system

Technical data

Order no.	1.576-107.0	
EAN code	4039784539310	
Current type	Ph / V / Hz	3 / 400 / 50
Air flow rate	l/s / m³/h	68 / 244.8
Vacuum	mbar / kPa	286 / 28.6
Container capacity	l	60
Rated input power / Amps	kW	3
Filter area	m²	1.9
Nominal diameter of connection	ID 70	
Nominal diameter of accessory	ID 70 / ID 50 / ID 40	
Sound pressure level	dB(A)	77
Weight	kg	95
Dimensions (L x W x H)	mm	970 x 690 x 1240

Equipment

Accessories in scope of delivery	No
---	----